

PRODUCT CODES: ELRX110-C

NAME: ENVIROKLEAN CONCENTRATE (3:7)

DESCRIPTION: ELRX110-C is a concentrated version of our EnviroKlean Water Based Cleaner that is packaged as an easy to use concentrate for economical and environmental shipping.

USES: This product, once diluted, is designed for cleaning belts on automated spray units, flushing pumps and fluid lines, as well as spray gun parts, mixing blades, hoses, spray booths, other metal surfaces or anything else that has paint on it. Do not leave painted items (guns/parts) submerged for more than 20 minutes or you risk damaging the finish.

PRODUCT PREPARATION: ELRX110-C should be diluted 3:7 with water. To make a full pail of ELRX110, use 6 parts concentrate and 14 parts water. There will be some turbidity in the solution when you mix water in, this is normal and expected.

RECOMMENDED APPLICATION: Once diluted, this product is ELRX110 and should be used in similar cleaning applications. Please refer to the product data sheet for ELRX110.

PHYSICAL PROPERTIES: (of the diluted product)	Specific Gravity:	0.97 +/-2%
	Viscosity:	NA (water thin)
	Solids Content:	None
	Pot Life:	None
	Flash Point:	>75 C
	VOC's:	328g/L, 2.73 lb/gal

GENERAL INFORMATION: These products are designed for industrial use only. Please refer to the Safety Data Sheet prior to use.

SHELF LIFE: 24 months in unopened containers

STORAGE: Store in a tightly closed container at room temperature (18-25°C/64-75°F) and protect from direct sunlight and foreign material.

Disclaimer: Every reasonable precaution is taken in the manufacture of our products to ensure that they comply with our standards. The information given herein is correct to the best of our knowledge. Any suggestions made by us covering the use of our products are based on experience and/or tests believed to be reliable. However, because the use of any product of our manufacture is completely beyond our control, including for example, the method and conditions of application, no guarantee or warranty, expressed or implied, is made. Manufacturer's maximum liability shall be to replace such quantity of product determined by our laboratory to be defective. User shall determine the suitability of the product for his intended use and assumes all risk and liability in connection therewith.