

# Safety Data Sheet

According to U.S.A. Federal Hazcom 2012

## 1. Identification

### 1.1. Product identifier

Code: **PMES325**  
 Product name: **ENVIROSTAIN 325 UNIFORM ANTIQUE WALNUT**

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses	Industrial	Professional	Consumer
<b>VARNISHING PRODUCTS</b>	✓	✓	-

### 1.3. Details of the supplier of the safety data sheet

Name: **Performance Finishing Solutions**  
 Full address: **4800 Eastgate Parkway, Units 3&4**  
 District and Country: **Mississauga, Canada, L4W 3W6**

Tel: **800-239-3824**  
 Fax: **905-629-7865**

e-mail address of the competent person responsible for the Safety Data Sheet: **sales@performancefinishingolutions.com**

### 1.4. Emergency telephone number

For urgent inquiries refer to **For any requirement contact 800-239-3824, 8-5, M-F**

## 2. Hazards identification

### 2.1. Classification of the substance or mixture

The product is not classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information.

Hazard pictograms: --  
 Signal words: --  
 Hazard statements: --  
 Precautionary statements:  
 Prevention: --  
 Response: --  
 Storage: --  
 Disposal: --

### 2.2. Other hazards

Additional hazards  
 Contains:  
 1,2-BENZISOTHIAZOL-3(2H)-ONE  
 May produce an allergic reaction.

## 3. Composition/information on ingredients

### 3. Composition/information on ingredients ... / >>

#### 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification:
<b>1-METHOXY-2-PROPANOL</b>		
INDEX 603-064-00-3	3.5 ≤ x < 4	<b>Flammable liquid, category 3 H226, Specific target organ toxicity - single exposure, category 3 H336</b>
EC 203-539-1		
CAS 107-98-2		
REACH Reg. 01-2119457435-35		
<b>2-(2-BUTOXYETHOXY)ETHANOL</b>		
INDEX 603-096-00-8	2.5 ≤ x < 3	<b>Eye irritation, category 2 H319</b>
EC 203-961-6		
CAS 112-34-5		
REACH Reg. 01-2119475104-44		

\* There is a batch to batch variation.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### 4. First-aid measures

#### 4.1. Description of first aid measures

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.  
**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.  
**INHALATION:** Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.  
**INGESTION:** Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

### 5. Fire-fighting measures

#### 5.1. Extinguishing media

**SUITABLE EXTINGUISHING EQUIPMENT**  
The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.  
**UNSUITABLE EXTINGUISHING EQUIPMENT**  
None in particular.

#### 5.2. Special hazards arising from the substance or mixture

**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**  
Do not breathe combustion products.

#### 5.3. Advice for firefighters

**GENERAL INFORMATION**  
Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.  
**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**  
Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## 7. Handling and storage

### 7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

## 8. Exposure controls/personal protection

### 8.1. Control parameters

Regulatory References:

USA	NIOSH-REL	NIOSH publication No. 2005-149, 3th printing, 2007.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022

### 1-METHOXY-2-PROPANOL

#### Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	184	50	368	100	
OEL	EU	375	100	568	150	SKIN
CAL/OSHA	USA	360	100	540	150	SKIN
NIOSH	USA	360	100	540	150	

**8. Exposure controls/personal protection ... / >>**
**2-(2-BUTOXYETHOXY)ETHANOL**
**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>	ppm	
TLV-ACGIH	-	66	10			INHAL
OEL	EU	67.5	10	101.2	15	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

**HAND PROTECTION**

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (OSHA 29 CFR 1910.138): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose limit of use will be defined by the manufacturer (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

**ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**9. Physical and chemical properties**
**9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	liquid	
Colour	dark brown	
Odour	characteristic	
Odour threshold	not available	
pH	7-9	
Melting point / freezing point	not available	
Initial boiling point	> 35 °C	(95 °F)
Boiling range	not available	
Flash point	101 °C	(213,8 °F)
Evaporation rate	not available	
Flammability	not available	
Lower inflammability limit	not available	
Upper inflammability limit	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Vapour pressure	not available	
Vapour density	not available	
Relative density	1,16 +/- 0,02	kg/l
Solubility	not available	
Partition coefficient: n-octanol/water	not available	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
Viscosity	not available	
Explosive properties	not available	
Oxidising properties	not available	

## 9. Physical and chemical properties ... / >>

### 9.2. Other information

Total solids (250°C / 482°F) 22,63 %

## 10. Stability and reactivity

### 10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

#### 1-METHOXY-2-PROPANOL

Dissolves various plastic materials.Stable in normal conditions of use and storage.

Absorbs and dissolves in water and in organic solvents. With air it may slowly form explosive peroxides.

### 10.2. Chemical stability

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

#### 1-METHOXY-2-PROPANOL

May react dangerously with: strong oxidising agents,strong acids.

#### 2-(2-BUTOXYETHOXY)ETHANOL

May react with: oxidising substances.May form peroxides with: oxygen.Develops hydrogen on contact with: aluminium.May form explosive mixtures with: air.

### 10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

#### 1-METHOXY-2-PROPANOL

Avoid exposure to: air.

#### 2-(2-BUTOXYETHOXY)ETHANOL

Avoid exposure to: air.

### 10.5. Incompatible materials

#### 1-METHOXY-2-PROPANOL

Incompatible with: oxidising substances,strong acids,alkaline metals.

#### 2-(2-BUTOXYETHOXY)ETHANOL

Incompatible with: oxidising substances,strong acids,alkaline metals.

### 10.6. Hazardous decomposition products

#### 2-(2-BUTOXYETHOXY)ETHANOL

May develop: hydrogen.

## 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

### 11.1. Information on toxicological effects

#### Metabolism, toxicokinetics, mechanism of action and other information

Information not available

#### Information on likely routes of exposure

##### 1-METHOXY-2-PROPANOL

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

##### 2-(2-BUTOXYETHOXY)ETHANOL

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**11. Toxicological information** ... / >>**1-METHOXY-2-PROPANOL**

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product. Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported.

**2-(2-BUTOXYETHOXY)ETHANOL**

May be absorbed by inhalation, ingestion and skin contact; is irritating for the skin and especially for the eyes. May cause damage to the spleen. At room temperature the danger of inhalation is unlikely, due to the low vapour pressure of the substance.

Interactive effects

Information not available

ACUTE TOXICITY**2-(2-BUTOXYETHOXY)ETHANOL**

LD50 (Oral):	3384 mg/kg Rat
LD50 (Dermal):	2700 mg/kg Rabbit

**1-METHOXY-2-PROPANOL**

LD50 (Oral):	5300 mg/kg Rat
LD50 (Dermal):	13000 mg/kg Rabbit
LC50 (Inhalation vapours):	54.6 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Contains:

1,2-BENZISOTHIAZOL-3(2H)-ONE  
May produce an allergic reaction.

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Carcinogenicity Assessment:

107-98-2	1-METHOXY-2-PROPANOL
	ACGIH:: A4
1330-20-7	XYLENE
	IARC:3
98-82-8	CUMENE
	IARC:2B

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

## 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

### 12.1. Toxicity

Information not available

### 12.2. Persistence and degradability

#### 2-(2-BUTOXYETHOXY)ETHANOL

Solubility in water 1000 - 10000 mg/l  
 Rapidly degradable

#### 1-METHOXY-2-PROPANOL

Solubility in water 1000 - 10000 mg/l  
 Rapidly degradable

### 12.3. Bioaccumulative potential

#### 2-(2-BUTOXYETHOXY)ETHANOL

Partition coefficient: n-octanol/water 1

#### 1-METHOXY-2-PROPANOL

Partition coefficient: n-octanol/water < 1

### 12.4. Mobility in soil

Information not available

### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

### 12.6. Other adverse effects

Information not available

## 13. Disposal considerations

### 13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.  
 Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.  
**CONTAMINATED PACKAGING**  
 Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

## 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

### 14.1. UN number

not applicable

**14. Transport information** ... / >>**14.2. UN proper shipping name**

not applicable

**14.3. Transport hazard class(es)**

not applicable

**14.4. Packing group**

not applicable

**14.5. Environmental hazards**

not applicable

**14.6. Special precautions for user**

not applicable

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Information not relevant

**15. Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**U.S. Federal RegulationsTSCA:

All components of this product are listed on US Toxic Substances Control Act (TSCA) Inventory or are exempt from the listing / notification requirements.

Clean Air Act Section 112(b):

107-98-2 1-METHOXY-2-PROPANOL (Glycol ethers)

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:

No component(s) listed.

Clean Water Act – Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:313 Category Code:

107-98-2 1-METHOXY-2-PROPANOL (Glycol ethers)

EPCRA 302 EHS TPQ:

No component(s) listed.



**15. Regulatory information** ... / >>

EPCRA 304 EHS RQ:  
No component(s) listed.

CERCLA RQ:  
No component(s) listed.

EPCRA 313 TRI:  
107-98-2 1-METHOXY-2-PROPANOL (Glycol ethers)

RCRA Code:  
No component(s) listed.

CAA 112 (r) RMP TQ:  
No component(s) listed.

State RegulationsMassachusetts:

107-98-2 1-METHOXY-2-PROPANOL (Glycol ethers)  
7631-86-9 AMORPHOUS SILICATE HYDRATE

Minnesota:

57-55-6 1,2-PROPANEDIOL  
107-98-2 1-METHOXY-2-PROPANOL (Glycol ethers)  
7631-86-9 AMORPHOUS SILICATE HYDRATE  
25322-69-4 PROPANE-1,2-DIOL, PROPOXYLATED

New Jersey:

57-55-6 1,2-PROPANEDIOL  
107-98-2 1-METHOXY-2-PROPANOL (Glycol ethers)

New York:

No component(s) listed.

Pennsylvania:

57-55-6 1,2-PROPANEDIOL  
107-98-2 1-METHOXY-2-PROPANOL (Glycol ethers)  
7631-86-9 AMORPHOUS SILICATE HYDRATE

California:

107-98-2 1-METHOXY-2-PROPANOL (Glycol ethers)  
7631-86-9 AMORPHOUS SILICATE HYDRATE

Proposition 65:

This product does not contain any substances known to the State of California to cause cancer, reproductive harm or birth defects.

International Regulations

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

**16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

**H319** Causes serious eye irritation.  
**H226** Flammable liquid and vapour.  
**H336** May cause drowsiness or dizziness.

## LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAA 112 © RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112©)

**16. Other information ... / >>**

- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: Regulation (EC) 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REACH: Regulation (EC) 1907/2006
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

**GENERAL BIBLIOGRAPHY:**

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy
  
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112© of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Department Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**CALCULATION METHODS FOR CLASSIFICATION**

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

